

39-MWFPP2F3-502X















39-MWFPP2F3-502X



Our Price: £494.99

Description Milwaukee M18 FPP2F3-502X Powerpack Impact Drill and Impact Wrench

New To Ernest Doe!

The M18FPP2F3-502X FUEL Twin Pack consists of the M18FPD3 Combi Drill with AUTOSTOP control mode for enhanced safety, the M18 FMTIW2F12 1/2" Impact Wrench with 4-Mode DRIVE CONTROL.

Milwaukee M18FPD3 Combi Drill Features-

Higher power efficiency under load - outstanding torque of 158 Nm

Extremely compact design of 175 mm length for access into tight spaces AUTOSTOP^{IM} Feature to Protect from over rotation in a bind up for enhanced safety, equipped with a dedicated autostop light on foot of tool to indicate a protection event Brushless POWERSTATE® motor for heavy application under load

REDLITION barry pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life Fastest Drilling and Driving applications under load

Individual battery cell monitoring optimises tool run time and ensures long term pack durability

Battery fuel gauge displays remaining charge

13 mm metal chuck for quick bit changes and bit retention

All metal reversible belt clip to hang your tool quickly and easily Flexible battery system: works with all MILWAUKEE® M18TMbatteries

Brighter LED workspace illumination

Milwaukee M18 FMTIW2F12 Impact Wrench Features-



39-MWFPP2F3-502X

Most versatile cordless impact wrench in the MILWAUKEE® impressive arsenal with an industry-leading performance at 881 Nm of nut-busting torque and 745 Nm of fastening torque

Incredibly compact design for this performance level, with only 152 mm overall length ideal for applications in tight spaces

4-Mode DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility

Bolt removal control delivers full torque output, then decreases RPMs once the bolt is loosened to prevent fastener drops Auto shut-off control applies no more than 47 Nm of torque for hand-tight fastening applications to prevent over-tightening

Tri-LEDs deliver high definition lighting to increase workspace visibility

1/2? square friction ring Reversible belt hook

Comes With:

1 X M18FPD3 Fuel Percussion Drill

- 1 X M18FMTIW2F12 Fuel Impact Wrench
- 2 X M18B5 5.0Ah Battery

1 X M12-18FC Charger 2 X HD-BOX

2 A HD-BUA

Product Specification:

Milwaukee M18FPD3 Combi Drill:

Chuck Capacity (mm): 13 Max. Drilling Masonry (mm): 16 Max. Drilling Steel (mm): 16 Max. Drilling Wood (mm): 89 Max. Percussion Rate (BPM): 0 - 33,000 Max. Torque (NM): 158 No Load Speed Gear 1 (RPM): 0 - 500 No Load Speed Gear 2 (RPM): 0 - 2100 Standard Equipment: Belt clip, side handle

Milwaukee M18 FMTIW2F12 Impact Wrench:

Impact Rate (IPM): 0-900 / 0-2100 / 0-3100 Max. Bolt Diameter: M22 Max. Fastening Torque (NM): 745 Max. Torque (NM): 475 / 610 / 745 / 47 No Load Speed (RPM): 0-1250 / 0-1950 / 0-2575 / 0-1325 Nut-Busting Torque (NM): 881 Tool Reception: ½? square Weight With Battery Pack (EPTA) (KG): 2.3 (M18 B5) Sound Power Level (LWA)(DB(A)): 106.4 Sound Power Level Uncertainty (DB(A)): 3 Sound Pressure Level (LPA)(DB(A)): 95.4 Sound Pressure Level Uncertainty (DB(A)): 3 Vibration Impact Tightening Of Fasteners Of The Maximum Capacity Of The Tool [M]S²]: 17.4



39-MWFPP2F3-502X Attributes

Technical Data

Battery capacity 12Ah

Contact us

Ernest Doe is a long established family firm with a network of branches in the South and East of England. Managing Director Colin Doe is the fourth generation of the family to have run the business in its 100+ years of trading.

The firm supplies an incredible amount of machinery; from garden mowers and chain saws to combine harvesters and construction excavators. Our philosophy is simple to supply the best products and then to support them with the service facilities and expertise to keep them running perfectly.

Tel. +44 (0)1245 383565

Ernest Doe & Sons Limited Ulting, Maldon, Essex CM9 6QH